

"FOR GUARANTEED TROUBLE FREE SERVICE"



SANT & SBM

V A L V E S

GUN METAL,
BRONZE,
CAST IRON &
STEEL VALVES

RETAIL PRICE LIST

List No. : SANT/RPL/ 01-2020

Dated : 15-01-2020

THIS CANCELS ALL OUR PREVIOUS PRICE LISTS.

GOODS & SERVICES TAX (GST @ 18%) EXTRA





Product : **Sant Cast Steel Globe Valve**
 Product Standard : **BS 5160/DIN 2401**
 Pressure/Class /Rating : **PN-40**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Bonnet O/S & Yoke type Rising Stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **Stainless Steel AISI-410**
 End Details : **Flanges as per BS 4504 Part-1/DIN 2545 RF undrilled**
 Body Test Pressure : **76barg (1100 Psig.) Hyd.**
 Seat Test Pressure : **40barg (580 Psig.) Hyd.**

CS 1

HSN CODE : 84818030

Size/Inch	mm	Price / Pc.
1/2	15	3813
3/4	20	4114
1	25	4814
1¼	32	6725
1½	40	8009
2	50	10256
2½	65	15521
3	80	20043
4	100	29542
5	125	41740
6	150	65414
8	200	118733
10	250	203016
12	300	270491



Product : **Sant Cast Steel Horizontal Check Valve**
 Product Standard : **BS 5160/DIN 2401**
 Pressure/Class /Rating : **PN-40**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Cover**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **Stainless Steel AISI-410**
 End Details : **Flanges as per BS 4504 Part-1/DIN 2545 RF undrilled**
 Body Test Pressure : **76barg (1100 Psig.) Hyd.**
 Seat Test Pressure : **40barg (580 Psig.) Hyd.**

CS 2

HSN CODE : 84813000

1/2	15	3743
3/4	20	3950
1	25	4547
1¼	32	5934
1½	40	6536
2	50	8848
2½	65	13196
3	80	17406
4	100	26034
5	125	37944
6	150	61213
8	200	115473
10	250	183178
12	300	258935



Product : **Sant Cast Steel Y-Type Strainer**
 Type of Pattern : **Y-Type**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Y-Type Bolted Cover**
 Trim : **SS (Type 304) Screen having 1.2mm dia perforation**
 End Details : **Flanges as per BS 10 Table J FF undrilled**
 Test Pressure : **700 Psig. Hyd. 49.23kg/cm²g**
 Working Pressure : **Max. BOP 350 Psig. at 400°C**

CS 3

HSN CODE : 84818030

1	25	5287
1½	40	9131
2	50	10687
2½	65	14262
3	80	19425
4	100	29532
5	125	41876
6	150	64616



Product : **Sant Cast Steel Y Type Strainer**
 Type of Pattern : **Y Type**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Cover 'Y' Type**
 Trim : **AISI 304, Screen 1.2mm dia perforation**
 End Details : **Flanges as per BS10 Table F/Class-150**
 Body Test Pressure : **40kg/cm² Hyd.**
 Maximum Working Pressure : **20kg/cm²**
 Maximum Working Temperature : **400°C**

CS 3A

HSN CODE : 84818030

1½	40	5085
2	50	7279
2½	65	8847
3	80	12583
4	100	16724
6	150	37691
8	200	52894



Product : **Sant Cast Steel Gate Valve**
 Product Standard : **Conforming to BS 1414/API-600**
 Type of Pattern : **Straight**
 Pressure/Class /Rating : **Class-300**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Bonnet O/S Yoke type Rising Stem**
 Type of Seat : **Renewable Seat**
 Type of Wedge : **Solid / Flexible**
 Trim : **SS AISI-410 with Aluminum Bronze Sleeve**
 End Details : **Flanges as per ASME B 16.5 Class 300 R.F., undrilled**
 Body Test Pressure : **76barg Hyd. (1110 Psig)**
 Seat Test Pressure : **56barg(815Psig.) Hyd. 6.9barg AIR (100Psig.)**

CS 7A

HSN CODE : 84818030

Size/Inch	mm	Price / Pc.
1½	40	13319
2	50	15980
2½	65	20628
3	80	24753
4	100	38231
5	125	62708
6	150	73525
8	200	111406
10	250	201330
12	300	310565



Product : **Sant Cast Steel Gate Valve**
 Product Standard : **Conforming to BS-1414/API 600**
 Type of Pattern : **Straight Type**
 Pressure / Class Rating : **Class 600**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Bonnet O/S Yoke Type Rising Stem**
 Type of Seat : **Renewable**
 Type of Wedge : **Solid/Flexible Wedge**
 Trim : **SS AISI-410 & Aluminium Bronze Sleeves**
 End Details : **Flanges as per ASME B 16.5 Class 600 RF Undrilled**
 Body Test Pressure : **153 Barg (2220 Psig.) Hyd.**
 Seat Test Pressure : **112 Barg (1630 Psig.) Hyd. 6.9barg 100 Psig. (AIR)**

CS 7B

HSN CODE : 84818030

1½	40	17820
2	50	28294
2½	65	35592
3	80	46763
4	100	76523
6	150	144569
8	200	232715



Product : **Sant Cast Steel Swing Check Valve**
 Product Standard : **Conforming to BS 1868/ANSI B 16.34**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Cover**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Hinge Pin : **AISI 410 Stainless Steel**
 End Details : **Flanges as per ASME B 16.5 Class-150 R.F. Undrilled**
 Body Test Pressure : **30barg Hyd. (435Psig.)**
 Seat Test Pressure : **22barg Hyd. (320Psig.)**

CS 8

HSN CODE : 84813000

1½	40	8357
2	50	11431
2½	65	16045
3	80	18452
4	100	26241
5	125	34630
6	150	39713
8	200	68190



Product : **Sant Cast Steel Globe Valve**
 Product Standard : **Conforming to BS 1873-1975 Class-150**
 Pressure/Class /Rating : **Class-150**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Bonnet O/S Yoke Type Rising Stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Stem : **SS AISI-410 component with Aluminum Bronze Yoke Bush**
 End Details : **Flanges as per ASME B 16.5 Class-150 Undrilled**
 Body Test Pressure : **30barg Hyd. (435Psig.)**
 Seat Test Pressure : **22barg Hyd. (320Psig.), 6.9 Barg Air (100 Psig.)**

CS 9

HSN CODE : 84818030

1	25	6249
1¼	32	8691
1½	40	10033
2	50	14078
2½	65	18050
3	80	23734
4	100	33695
6	150	61731
8	200	92643
10	250	150082
12	300	220495



Product : **Sant Cast Steel Globe Valve**
 Product Standard : **Conforming to BS 1873-1975 Class-300**
 Pressure/Class /Rating : **Class-300**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Bonnet O/S Yoke type Rising Stem**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410 component with Aluminum Bronze Yoke Bush**
 End Details : **Flanges as per ASME B 16.5 Class-300 Undrilled**
 Body Test Pressure : **76barg Hyd. (1102 Psig.)**
 Seat Test Pressure : **56barg Hyd. (815Psig.) 6.9barg (100Psig.) AIR**

Size/Inch	mm	Price / Pc.
1	25	7287
1¼	32	10257
1½	40	11295
2	50	14841
2½	65	23476
3	80	27122
4	100	39126
6	150	71783
8	200	106865
10	250	254397
12	300	332159

CS 10

HSN CODE : 84818030



Product : **Sant Cast Steel Horizontal Check Valve**
 Product Standard : **BS 1868**
 Pressure / Class Rating : **Class 300**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Bonnet**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410**
 End Details : **Flanges as per ASME B 16.5 Class 300 Undrilled**
 Body Test Pressure : **76 Barg (1102 Psig.) Hyd.**
 Seat Test Pressure : **56 Barg (815 Psig.) Hyd. 6.9 Barg (100 Psig.) AIR**

1	25	4865
1¼	32	5972
1½	40	7535
2	50	10172
2½	65	16533
3	80	20503
4	100	29643
6	150	59185
8	200	88655
10	250	152967
12	300	221984

CS 8A

HSN CODE : 84813000



Product : **Sant Cast Steel Globe Valve**
 Product Standard : **BS 1873**
 Pressure / Class Rating : **Class 600**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Bolted Bonnet O/S Yoke Type Rising Stem**
 Type of Seat : **Renewable**
 Type of Disc : **Renewable Disc**
 Trim : **SS AISI-410**
 End Details : **Flanges as per ASME B 16.5 Class 600 RF Undrilled**
 Body Test Pressure : **153 Barg (2220 Psig.) Hyd.**
 Seat Test Pressure : **112 Barg (1630 Psig.) Hyd. 6.9barg 100 Psig. (AIR)**

1½	40	16092
2	50	24130
2½	65	32825
3	80	42602
4	100	73087
6	150	163576
8	200	295099

CS 10A

HSN CODE : 84818030



Product : **Sant Cast Steel Ball Valve**
 Product Standard : **BS 5351/ API 6D**
 Type of Pattern : **Straight Type**
 Pressure/Class /Rating : **Class-150**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Three Piece design Lever Operated**
 Type of Seat : **Renewable Seat**
 Trim : **Stem: 13% Cr. Steel ASTM A-276 Type-410**
 Ball : SS (ASTM A 351 Gr. CF 8/AISI-304)
 Seat Ring & Gland Packing PTFE
 End Details : **Flanges as per ASME B 16.5 Class 150 R.F., undrilled**
 Body Test Pressure : **30barg Hyd. (435 Psig)**
 Seat Test Pressure : **22barg(320Psig.) Hyd. 6.9barg AIR (100 Psig.)**
 Maximum Working Temperature : **250°C**

1	25	3198
1½	40	5732
2	50	7679
2½	65	10953
3	80	13904
4	100	22313

CS11

HSN CODE : 84818030



Product : **Sant Cast Steel Single Post Full Lift Safety Valve**
 Type of Pattern : **Right Angle**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description : **Spring Loaded Full Lift**
 Type of Seat : **Renewable Seat**
 Type of Disc : **Renewable Disc**
 Trim : **SS to AISI 304**
 End Details : **Inlet Flanges to BS 10 Table-H**
 Outlet Flanges to BS 10 Table-E
 Body Test Pressure : **53kg/cm²g Hyd.**
 Maximum Working Pressure : **26.5kg/cm²g**
 Maximum Working Temperature : **425°C**

CS 12

HSN CODE : 84814000

Size/Inch	mm	Price / Pc.
1 x 2	25 x 50	17803
1½ x 2	40 x 50	24805
1½ x 3	40 x 80	27718
2 x 3	50 x 80	37777
3 x 4	80 x 100	56893



Product : **Sant Cast Steel Moisture Separator**
 Body Material cum standard : **CCS (ASTM A-216 Gr. WCB)**
 Product Description :
 End Details : **Flanges as per BS10 Table F**
 Body Test Pressure : **40kg/cm² Hyd.**
 Maximum Working Temperature : **20kg/cm²**

CS 13

HSN CODE : 84818030

1	25	4691
1½	40	6951
2	50	11554
2½	65	16176
3	80	18594
4	100	35879

TERMS & CONDITIONS

1. Your Orders/Indents will be supplied on rates prevailing at the time of dispatch.
2. All orders placed direct or through Agent are valid only after confirmation from Head Office.
3. Rates are Ex-works, Jalandhar and inclusive of packing charges.
4. Every precaution is being taken while packing the goods which are generally booked at Railway/
5. Transport Risk but in case of any damage, loss or pilferage in transit we are not liable to accept any responsibility. Carriers would be considered as Indentor's Agent after a consignment is handed over by us to the former. Any Claim due to losses in transit or wrong delivery shall be concern between indentor and his carriers.
6. Order once placed and confirmed by us cannot be cancelled without our consent. We reserve the right to execute any order in full or in parts according to our supply position or manufacturing capacity. We accept no liabilities for delayed supplies for reasons beyond our control such as war, lockout breakdown or riots, etc. All commitments entered into by us are subject to above contingencies beyond our control.
7. Each consignment despatched contains Packing Slip. Any Shortage found in package received intact, should be reported to us for verification with in 7 DAYS from the date of taking delivery. Unless otherwise agreed upon all Way Bills or Railway Receipts for goods supplied shall be negotiated through scheduled Bank against payment only or per V.P.P.
New customers are requested to remit 25% of the value of the order as advance.
8. **Goods & Services Tax (GST@18%) will be charged extra as applicable.**
9. All disputes arising out of an order placed direct or through an Agent will be Subject to Jurisdiction of Law Courts at Jalandhar.
10. Rates & Terms are subject to alteration without notice.

-: NOTE :-

**ALL FLANGED VALVES ARE SUPPLIED UNDRILLED
UNLESS SPECIFIED BY THE INDENTOR**